NAS OS ADMINISTRATION

All LaCie NAS feature an easy-to-use browser-based administration tool, called the **Dashboard**. Launch the Dashboard to manage storage, users, shares, and much more.

ACCESS THE DASHBOARD

There are two ways to access the Dashboard: LaCie Network Assistant and an internet browser.

Access the Dashboard: LaCie Network Assistant

See <u>LaCie Network Assistant</u> for instructions on software installation.

1. **Windows:** Right-click on the LaCie Network Assistant icon in the system tray (Windows users). **Mac:** Choose the LaCie Network Assistant icon in the menu bar.





- 2. Select [machine name] > Web Access.
- 3. The login page will open in a new browser window or tab. If your browser is not open, LaCie Network Assistant will open it for you.

Access the Dashboard: Internet browser

- 1. Launch your preferred internet browser and type the default address for the LaCie NAS:
 - Windows workstations (no Bonjour) http://lacie-2big-nas or http://lacie-5big-pro
 - Mac OS X and Windows workstations running Bonjour http://lacie-2big-nas.local or http://lacie-5big-pro.local.

$(\rightarrow) \textcircled{http://lacie-5big-pro.local/ } \rightarrow \times \textcircled{aCie Login}$	×	
LACIE 5big NAS Pro		

You can also type your LaCie NAS's IP address in the browser's URL (web address) field. For example: **http://[IP-address]**.

LaCie Login ×	
LACIE 5big NAS Pro	
	Connect to LaCie-5big-Pro
0	Login
	Password
	Log on
	>> Switch to https

The IP address may be found in LaCie Network Assistant (see Find the IP Address).

LOG IN

The first time you access the Dashboard, complete the *Authentication* and *Timezone* fields. (The password should be from 4-20 alphanumeric characters and symbols, and the username should be from 1-20 alphanumeric characters. Consider using a strong password that is difficult for others to guess.)

1. Update	2. S	ettings	3. Share recovery
Authentication			
Product name	LaCie-2big-NAS		
	To identify your 2big NAS	S on your local network.	
Administrator login	admin		
Password	•••••		
Confirm your password	•••••	0	
Timezone			
Suggestions (GMT+01:00) Amsterdam, Berli (GMT+01:00) Belgrade, Bratisla	n, Rome, Stockholm, Vienna Iva, Budapest, Prague	^	
(GMT+01:00) Sarajevo, Skopie, All Time Zones (GMT-12:00) Eniwetok, Kwajale (GMT-11:00) Samoa Standard	ingen, Midway Is.	~	

In subsequent logins, simply enter your username and password, then choose **Log on**.



For added security, choose **Switch to HTTPS** at the Dashboard login.

Recover a lost password

If a user has forgotten his/her password, it can be recovered if the administrator has:

- Assigned an SMTP server (see <u>Support</u>).
- Entered an email address for that user (see <u>Users</u>).

If the above conditions have been met, the administrator and/or user can follow the steps below to recover a password:

1. On the login page, choose **Have you lost or forgotten your password?**.

LACIE 5big NAS Pro	
	Connect to LaCie-5big-Pro
0	Login Password
	Remember me
	Log on
	Have you lost or torgotten your password? >> Switch to https

2. On the next page, type the login. Then type the word you see in the image on the right (this ensures that the request is coming from a person) and choose **send**.

Login	admin	
Word verification	Write the characters exactly as they appear	angle
	angle	Try a new word

- 3. The email will arrive in the user's email inbox. In the email, choose the **click here** link.
- 4. In the **Reinitialize your password** screen, type your login and new password, then choose **Send**.

Restart, deep sleep mode, and shutdown

To restart or put the LaCie NAS into deep sleep mode, select the power button, then choose between **Restart** and **Deep Sleep mode**. Deep sleep mode must be enabled or the option will not be available (see <u>Eco</u><u>Management</u>).



2big NAS Restart and Deep Sleep Mode



5big NAS Pro Deep Sleep Mode, Restart, and Shutdown

The LaCie 5big NAS Pro has the added option to **Shutdown** the device. To shut down the LaCie 2big NAS, use the switch on the back of the device (see <u>Views of the Product</u>).

Note: Shut down your LaCie NAS only when it is not being accessed.

Log out

To log out of the Dashboard, choose the log out button.



NAVIGATE THE DASHBOARD

LACIE 5big NAS	Pro		ô b ō.	୰⊡
Dashboard			L Users	×
General Settings		Network	11 Us In 6 gr	sers oups
LUSers	1	Groups	< Shares	2 ×
Shares	1	O Backup	4 Sha	ares
Download	1	Storage	1 public	share
Eco management	d	Support	Storage	×
- M→ Hardware monitoring			RAID 5	3.9 TB
	-		ISCSI	0
Con Workgroup Contact Stress Contact	Retwork 2 × IP address 2 10.21.57.149 Direct Internet connection LaCle MyNAS Automatic port forwarding	Hardware monitoring	×	9 ø 3

The Dashboard is made up of:

- 1. The central pane that hosts all management pages
- 2. Visible widgets, or small boxes that represent the different pages. A visible widget provides a summary of the page's management function. For example, the *Hardware monitoring* shows the health status of the NAS, including the Temperature, Fan, and Drive states.
- 3. Minimized widgets

NAVIGATION

• To **navigate to a page**, choose its widget or, drag and drop the widget to the center of the window.

+ onuroo						_	Losers	
Name C	Description	Volume	2	2	Protocols			
NetBackup		RAID 5	0	0	•	di l	11 Users	
Photos		RAID 5	0	1	•	di la	In 6 groups	
Public		RAID 5	Public	Public	•	B		
admin		RAID 0	0	1	•	Ø		
							Storage	
							RAID 0	3.0.1
								0.0
							RAID 5	3.9 T
							RAID 5	3.9
General Settings	X B Net	work	× 14	Hardware	a monitoring	, ×		3.9
General Settings	X S Net	work 15 10.21.1	× Jy. 57.149	Hardware	a monitoring	, ×		3.9 •
General Settings Cle-Sbig-Pro Workgroup 31	X Paddres WED. Direct Int Direct Int	twork is 10.21.1 erret connection	× J ₄ , 57.149	Hardware	a monitoring Temperature Fan	, ×		3.9 •
General Settings	X Paddres WED, JULY 2013 Automation	work ss 10.21.1 emet connection /NAS c port forwarding	× J ₄ , 57.149	Hardware	e monitoring Temperature Fan Drive	, X •		3.9 •

• To **minimize a widget**, choose the **X** next to its title.

LACIE 5big NAS	Pro					ô t o.	0E
< Shares				dd share	0	LUSers	×
Name Descri	ption Volume	2.	1	Protocols			
NetBackup	RAID 5	0	0	0	Ø	11 Users	
Photos	RAID 5	0	1	٠	1		
Public	RAID 5	Public	Public		Ø		
admin	RAID 0	0	1		1		_
						4 Shares 1 public share	0
						Storage	×
						RAID 0	
						PAID 6	
General Settings X	Retwork	×	Hardware	monitoring	×		
aCie-5big-Pro In Workgroup 31 JULY 2013 11:06	IP address 10.21. Direct Internet connection LaCle MyNAS Automatic port forwarding	57.149	Э	Temperature Fan Drive	0 0 0		Q &

- To expand a minimized widget, drag its icon over an expanded widget, or to an open widget space.
- To **rearrange widgets**, drag the minimized widget icon or the expanded widget onto the place of another widget.